



ALTRON NEFT 5W-40 SP A3/B4

DESCRIPTION

All-season synthetic motor oil created on the basis of hydrocracked base oils with the addition of PAO and esters.

It ensures exceptional engine cleanliness, protection against premature self-ignition of the fuel-air mixture (LSPI effect), and prevention of deposits formation.

APPLICATION

Recommended for use in modern passenger cars with gasoline or diesel engines, including turbocharged engines, where ACEA A3/B4 or API SP/CF (and lower) performance levels are required.

SPECIFICATIONS & APPROVALS

Specification	Value
SAE	5W-40
API	SP
ACEA	A3/B4
PSA	B71 2296
Porsche	A40
Renault	RN 0700, RN 0710
Mercedes-Benz	229.5 / 229.3 / 226.5

Specification	Value
BMW	Longlife-01

PACKAGING

Volume	Article No.	Barcode
1 L	AMO0055	4630086736614
4 L	AMO0056	4630086736621
5 L	AMO0057	4630086736638
60 L	AMO0058	4630086736645
180 L	AMO0059	4630086736669

PHYSICO-CHEMICAL PROPERTIES

Property	Method	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	15.10
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	89.95
Viscosity index	ASTM D2270	178
HTHS viscosity at 150 °C, mPa·s	ASTM D4683	3.9
Dynamic viscosity CCS at -30 °C, mPa·s	ASTM D5293	5230
Dynamic viscosity MRV at -35 °C, mPa·s	ASTM D4684	33280
Noack volatility, %	ASTM D5800	9.5
Flash point, °C	ASTM D92	221
Pour point, °C	ASTM D97	-49
TBN, mg KOH/g	ASTM D2896	11.4
Sulfated ash, %	ASTM D874	1.2

HEALTH AND SAFETY

When used as recommended and in compliance with personal and industrial hygiene rules, ALTRON NEFT ASTRA 5W-40 SP A3/B4 presents no health or environmental hazards.

Avoid prolonged skin contact. In case of contact, wash with soap and water. Refer to the Safety Data Sheet for detailed information.

ENVIRONMENTAL PROTECTION

Used oil and product residues must be collected in a sealed container.

Dispose of waste oils only through authorized collection points.

Do not discharge into drains, soil, or water bodies.
